



AD		
A 17		
~		

TECHNICAL REPORT ARCCB-TR-87019

OTIC FILE (C)

THE C² CONTINUITY OF PIECEWISE CUBIC HERMITE POLYNOMIALS WITH UNEQUAL INTERVALS

AD-A183 351

C. N. SHEN

JULY 1987





AND ENGINEERING CENTER OLOGE COMPARA ARMAN ARMAN CENTER

CLOSE COMBAT ARMAMENTS CENTER BENÉT WEAPONS LABORATORY WATERVLIET, N.Y. 12189-4050

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED

REPORT DOCUMENTATION PAGE	READ INSTRUCTIONS BEFORE COMPLETING FORM		
ARCCB-TR-87019	3. RECIPIENT'S CATALOG NUMBER		
4. TITLE (and Subtrice) THE C2 CONTINUITY OF PIECEWISE CUBIC HERMITE POLYNOMIALS WITH UNEQUAL INTERVALS	5. TYPE OF REPORT & PERIOD COVERED Final 6. PERFORMING ORG. REPORT NUMBER		
7. AUTHOR(a) C. N. Shen	S. CONTRACT OR GRANT NUMBER(*)		
9. PERFORMING ORGANIZATION NAME AND ADDRESS US Army ARDEC Benet Weapons Laboratory, SMCAR-CCB-TL Watervliet, NY 12189-4050	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS AMCMS No. 6111.01.91A0.0 PRON No. 1A6AZ601,NMLC		
11. CONTROLLING OFFICE NAME AND ADDRESS US Army ARDEC	12. REPORT DATE July 1987		
Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000 14. MONITORING AGENCY NAME & ADDRESS(If different from Controlling Office)	13. NUMBER OF PAGES 12		
14. MONITORING AGENCY NAME & ADDRESS(II different from Controlling Office)	18. SECURITY CLASS. (of this report) UNCLASSIFIED 18a, DECLASSIFICATION/DOWNGRADING SCHEDULE		
16. Distribution STATEMENT (of this Report) Approved for public release; distribution unlimit	ed.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different fro	m Report)		
Presented at the Fourth Army Conference on Applie Cornell University, Ithaca, New York, 27–30 May 1 Published in Proceedings of the Conference.	d Mathematics and Computing, 986.		

18. KEY WORDS (Continue on reverse side if necessary and identify by block number)

Hermite Polynomials Spline Functions Data Smoothing Laser Vision System

A ABSTRACT (Continue on reverse side If nessenary and identify by block number)

Cubic hermite polynomials are usually C²_u continuous. With the introduction of smoothing within the intervals, the second derivatives can be made continuous. This may be applied to the autonomous vehicle problem with unequal laser scanning.

In using a laser range finder to measure the range, the direction of these laser rays can be subjected to angular errors. These errors, in the direction of these laser rays can be subjected to angular errors.

DD 1284 78 1473 EDITION OF 1 NOV 65 IS OBSOLETE

20.	ABS	TRACT	(CONT	' D)									
 by	igati the s	on of pline	auton funct	omous ion mo	vehi ethod	cles.	A no cubic	: hermit	m grid	may be nomials	employ For	ed to the pu	compute irpose the Aystens,
													!
_													

SECURITY CLASSIFICATION OF THIS PAGE(When Date Ent

85323/III 24.24444 (P1992 ZESENI PSESENANO) (PSESESENANO)

TABLE OF CONTENTS

	rage
INTRODUCTION	1
RECURSIVE FILTERING AND SMOOTHING PROCEDURE	1
EXAMPLE FOR C2 CONTINUITY	4
CONCLUSION	6
REFERENCES	7
APPENDIX	8

	The second secon	1
Access	ion For	
NTIS DTIC T Unanno Justif	AB 🔲	
	ibution/	-
Avai	lability Codes	-4
Dist	Avail and/or Special	DTIC COPY INSPECTED
MI		

ት የተሰር ካር ትር ጉር ትር ትር ጉር የሚገር የሚገር የሚገር የሚገር ሊተር አንርን ሊተር አር <mark>ታለር ታር ውር ውር ውር መስከት የመስከት መስከት መስከት መስከት መስከት መ</mark>ስከት መ

INTRODUCTION

The smoothing of gradients can be obtained by using an optimization method for approximation involving spline functions. A nonuniform grid may be employed to compute by the spline function method with cubic hermite polynomials. Continuous second derivatives at the grid point from both sides are essential for the purpose of smoothing. This method can be applied to solve the following problems: whether the platform can climb on the estimated in-path slope or whether it will tip over the estimated cross-path slope.

RECURSIVE FILTERING AND SMOOTHING PROCEDURE

A spline function $s(\xi)$ is a solution to the optimization problem

$$J^* = Min. \begin{cases} \sum_{i=1}^{N} [h(\beta_i) - m_i]^T R_i [h(\beta_i) - m_i] + \rho \sum_{i=2}^{N} [h]^2 d\xi \end{cases}$$

$$h \in C^2 \quad i=1$$

$$(1)$$

where for clarity and simplicity in discussion, we only consider the cubic spline case. A higher order polynomial spline can also be treated in a similar manner with more complicated computations.

A cubic spline, s, is a piecewise polynomial of class C² which has many good properties, such as the minimum norm property and local base property (refs 1,2). From the approximation theory, we know that for each set $A = \{a_1, \ldots, a_N, a_1, a_1, a_1, a_1, a_1\}$, there exists a unique cubic spline $s(\xi; A)$ such that

$$s(\beta_1;A) = a_1, \quad i = 1,2,...,N$$
 (2)

$$\dot{s}(\beta_i;A) = a'_i, i = 1,N$$
 (3)

where s is the first derivative of the function s. The above equations can be

Ahlberg, J. H., Nilson, E. N., and Walsh, J. L., <u>The Theory of Splines and Their Applications</u>, Academic Press, Inc., 1967.

²Schumaker, L. L., <u>Spline Functions: Basic Theory</u>, John Wiley & Sons, 1981.

thought of as boundary conditions for the piecewise cubic spline interpolation given a set of data (β_i, a_i) , for i = 1, 2, ..., N. Thus, solving the problem in Eq. (1) is equivalent to determining a set of constraints A for the optimization problem:

$$J^* = Min \left\{ \sum_{i=1}^{N} [s(\xi_i; A) - m_i]^T R_i^{-1} [s(\xi_i; A) - m_i] + \rho \sum_{i=2}^{N} \int_{\beta_{i-1}}^{\beta_{i-1}} [s(\xi; A)]^2 d\xi \right\}$$
(4)

Instead of taking a direct approach to find an optimal set of constraints for the problem above, it is proposed to further transform this problem into a form which is convenient to be solved. From the theory of numerical analysis (ref 3), it is well known that a piecewise cubic Hermite polynomial $p(\xi)$ is in the family of C¹. For each set $B = AuA^C$, where A^C is a complement of A, i.e., $A^C = \{a'_1, i = 2,3,...,N-1\}$, then $B = \{a_1,a'_1, i=1,2,...,N\}$, there exists a unique piecewise cubic Hermite polynomial $p(\xi;A)$ such that

$$p(\beta_i; B) = a_i , i = 1, 2, ..., N$$
 (5)

$$p(\beta_i; B) = a'_i , i = 2,..., N$$
 (6)

where p is the first derivative of p.

It should also be noted that for each set A, there are an infinite number of piecewise Hermite polynomials $p(\xi;A)$ such that

$$p(\beta_i;A) = a_i , i = 1,2,...,N$$
 (7)

$$\dot{p}(\beta_i;A) = a'_i , i = 1,N$$
 (8)

Let a set of $p(\xi;A)$ which satisfies the constraints in the equations above be P, i.e.,

$$P = \{p(\xi;A): (5), (6) \text{ satisfied}\}$$
 (9)

Burden, R. L. et al., <u>Numerical Analysis</u>, Prindle, Weber, & Schmidt, 1978.

Referring to the paper by de Boor (ref 4), it is noted that there exists a unique cubic spline $s(\xi;A)$ in the set P. Also from the minimum norm property of a cubic spline, we have the following relation:

$$\begin{array}{cccc}
N & \beta_{i} & \dots & N & \beta_{i} & \dots \\
\Sigma & \int & [s(\xi;A)]^{2} \leqslant \Sigma & \int & [p(\xi;A)]^{2} \\
i=2 & \beta_{i-1} & & i=2 & \beta_{i-1}
\end{array} \tag{9}$$

That is

$$\begin{array}{cccc}
N & \beta_{i} & \dots \\
\Sigma & \int & [s(\xi;A)]^{2} = \inf & J_{p}(p) \\
i=2 & \beta_{i-1} & p \in P
\end{array} \tag{10}$$

where

$$J_{p} = \sum_{i=2}^{N} \int_{\beta_{i-1}}^{\beta_{i}} [p(\xi;A)]^{2}$$
(11)

Since a cubic spline $s(\xi;A)$ is unique, a piecewise cubic Hermite polynomial $p(\xi;A)$ which minimizes the smoothing integral J_p in the above equation with respect to A^c becomes a cubic spline $s(\xi;A)$. To be more precise, we have the following theorem.

THEOREM: Let P represent a set of piecewise cubic Hermite polynomials p which satisfies the constraints below:

$$p(\beta_i; A^c) = a_i , i = 1, 2, ... N$$
 (12)

$$\dot{p}(\beta_i; A^c) = a'_i , i = 1, N$$
 (13)

The state of the s

where p \in C1, A, and AC are the same as mentioned before. Then there exists a unique cubic spline $s(\xi)$ such that

where s and p are the second derivatives of functions s and p and s \in C². A simple example with N = 3 is given next.

de Boor, C., "Bicubid Spline Interpolation," J. Math Phys., Vol. 41, 1962, pp. 212-218.

EXAMPLE FOR Cª CONTINUITY

For convenience and simplicity, we only consider a special case with N = 3. The node points are given as β_1 , β_2 , and β_3 . The intervals are not equal, i.e.,

$$(\beta_2 - \beta_1) \neq (\beta_3 - \beta_2) \tag{15}$$

Let a set of piecewise cubic Hermite polynomials p be

$$P = [p(t;A^{C}), p \in C^{1}[t_{1},t_{3}], p(t_{2}) = a, a \in A^{C}]$$
 (16)

which satisfies the constraints in the equations below:

$$p(t_i;A^c) = a_i$$
 , for $i = 1,2,3$ $\dot{p}(t_i;A^c) = a_i^t$, for $i = 1,3$ (17)

In this special case, a set $A^{C} = a'_{2} = a$.

We want to show here that the cubic Hermite polynomial $p(t;A^C)$, which is obtained by minimizing the smoothing integral, will become a cubic spline function $s(t) \in C^2[t_1,t_3]$

$$J^* = \underset{AC}{\text{Min}} \left\{ \int_{t_1}^{t_2^-} [p(t;A^2)]^2 dt + \int_{t_2^+}^{t_3} [p(t;A^C)]^2 dt \right\}$$

$$= \underset{a}{\text{Min}} \left\{ \int_{t_1}^{t_2^-} [p(t;a)]^2 dt + \int_{t_2^+}^{t_3} [p(t;a)]^2 dt \right\} \qquad (18)$$

From Eq. (A14) of the Appendix, the smoothing integral above can be written as

$$J(a) = (x_2 - A_1 x_1)^T B_1^{-1} (x_2 - A_1 x_1) + (x_3 - A_2 x_2)^T B_2^{-1} (x_3 - A_2 x_2)$$
(19)

where A_i , B_i^{-1} , and x_i are defined in the Appendix, and

$$x_i = (a_i, a_i)^T$$
, with $a_2 = a$, $i = 1, 2, 3$ (20)

$$\Delta_{i-1} = d_{i-1} = t_i - t_{i-1}$$
 (21)

Using Eqs. (All) and (Al2), the functional J(a) is written as

$$\begin{bmatrix} \begin{bmatrix} a_2 \\ a \end{bmatrix} & \begin{bmatrix} 1 & d_1 \\ 0 & 1 \end{bmatrix} \begin{bmatrix} a_1 \\ a'_1 \end{bmatrix} \end{bmatrix} \begin{bmatrix} 1 & -3 & -6d_1^2 \\ -6d_1^2 & 4d_1^2 \end{bmatrix} \begin{bmatrix} \begin{bmatrix} a_2 \\ a \end{bmatrix} - \begin{bmatrix} 1 & d_1 \\ 0 & 1 \end{bmatrix} \begin{bmatrix} a_1 \\ a \end{bmatrix} \end{bmatrix}$$

$$+ \left[\begin{bmatrix} a_3 \\ a'_3 \end{bmatrix} - \begin{bmatrix} 1 & d_2 \\ 0 & 1 \end{bmatrix} \begin{bmatrix} a_2 \\ a \end{bmatrix} \right] \begin{bmatrix} 1 & d_2 \\ -6d_2 \end{bmatrix} \begin{bmatrix} -2 & -6d_2 \\ -6d_2 \end{bmatrix} \begin{bmatrix} a_3 \\ -4d_2 \end{bmatrix} \begin{bmatrix} a_3 \\ -6d_2 \end{bmatrix} - \begin{bmatrix} 1 & d_2 \\ -6d_2 \end{bmatrix} \begin{bmatrix} a_3 \\ -6d_2 \end{bmatrix} \begin{bmatrix}$$

$$J(a) = 12d_{1}^{-3} (a_{2}-a_{1}-d_{1}a'_{1})^{2} - 12d_{1}^{-2} (a_{2}-a_{1}-d_{1}a'_{1})(a-a'_{1})$$

$$+ 4d_{1}^{-1} (a-a'_{1})^{2} + 12d_{2}^{-3} (a_{3}-a_{2}-d_{2}a)^{2}$$

$$-12d_{2}^{-2} (a_{3}-a_{2}-d_{2}a)(a'_{3}-a) + 4d_{2}^{-1} (a'_{3}-a)^{2}$$
(22)

Taking the partial derivative with respect to a yields

$$\frac{\partial J}{\partial a} = -12d_1^{-2} (a_2 - a_1 - d_1 a'_1) + 8d_1^{-1} (a - a'_1)$$

$$+ 24d_2^{-3} (a_3 - a_2 - d_2 a)(-d_2) - 12d_2^{-3} (-d_2)(a'_3 - a)$$

$$-12d_2^{-2} (-1)(a_3 - a_2 - d_2 a) - 8d_2^{-1} (a'_3 - a) = 0$$
(23)

Solving the equation above for a, one obtains

$$a^* = [3d_1^{-2}(a_2-a_1)-d_1^{-1}a'_1+3d_2^{-2}a_3-d_2^{-2}3a_2-d_2^{-1}a'_3]/[2(d_1^{-1}+d_2^{-1})]$$
(24)

To show that $p(t;a*)\in C^2[t_1,t_3]$, we only need to show that

$$\lim_{t \to t_2^-} p(t; a^*) = \lim_{t \to t_2^+} p(t; a^*) \tag{25}$$

That is, for a piecewise cubic Hermite polynomial p,

$$p_{1,2}(t_2;a^*) = p_{2,3}(t_2;a^*)$$
 (26)

where $p_{1,2}$ is the cubic Hermite polynomial within the interval β_1 and β_2 , and $p_{2,3}$ is the cubic Hermite polynomial within the interval β_2 and β_3 .

Now from the definition of piecewise cubic Hermite polynomial in the Appendix, we have

$$p_{1,2}(t_2;a^*) = 6d_1^{-2}(a_1-a_2) + 2d_1^{-1}a'_1 + 4_1^{-1}a^*$$
 (27)

By using Eq. (24), the above equation can be expressed as

$$p_{1,2}(t_2;a^*) = [-6a_2(d_1^1+d_2^1) + 6(a_1d_1^1+a_3d_2^1) + 2(a_1^1-a_3^1)]/(d_1+d_2)$$
 (28)

In a like manner, omitting the detailed derivation, we obtain easily

$$p_{2,3}(t_2;a^*) = [-6a_2(d_1^1+d_2^1) + 6(a_1d_1^1+a_3d_2^1) + 2(a_1^1-a_3^1)]/(d_1+d_2^1)$$
(29)

Thus, Eq. (26) is always true, that is, the conclusion in the theorem is valid. It is proved that the C² continuity exists in the optimization procedure for piecewise cubic Hermite polynomials with unequal intervals.

CONCLUSION

For scanning in the direction of elevation angle from the top of a mast where a laser is located, the intervals needed in angles are small for far away targets, while the same are large for close-by objects. The smoothing algorithm discussed in this report indicates that piecewise cubic Hermite polynomials can be used for unequal intervals or nonuniform grids.

REFERENCES

- 1. Ahlberg, J. H., Nilson, E. N., and Walsh, J. L., <u>The Theory of Splines and Their Applications</u>, Academic Press, Inc., 1967.
- 2. Schumaker, L. L., Spline Functions: Basic Theory, John Wiley & Sons, 1981.
- 3. Burden, R. L. et al, <u>Numerical Analysis</u>, Prindle, Weber, & Schmidt, 1978.
- 4. de Boor, C., "Bicubid Spline Interpolation," J. Math Phys., Vol. 41, 1962, pp. 212-218.

APPENDIX

EVALUATION OF THE SMOOTHING INTEGRAL

A piecewise cubic Hermite polynomial in the interval $[\beta_{i-1}, \beta_i]$ is represented in terms of the basis functions and the state vectors x_i , x_{i-1} , where the state vectors are defined as in Eq. (20). By changing the independent variable below,

$$t = \xi - \beta_{i-1} \tag{A1}$$

Then the smoothing integral in the interval $[\beta_{i-1}, \beta_i]$ becomes

$$I_{i-1,i} = \int_{0}^{\Delta_{i-1}} [p_{i-1,i}(t)]^2 dt$$
 (A2)

where $\Delta_{i-1} = t_i - t_{i-1} = \beta_i - \beta_{i-1}$, $\Delta_{i-1} \neq \Delta_i$.

With the change of the variable above, the second derivative of the Hermite polynomial can be written as

$$p_{i-1,i}(t) = \begin{bmatrix} ... \\ \phi_{i,i}(t) \\ ... \\ \psi_{i,1}(t) \\ ... \\ \phi_{i,0}(t) \\ ... \\ \psi_{i,0}(t) \end{bmatrix} \begin{bmatrix} x_i \\ x_{i-1} \end{bmatrix}$$
(A3)

where the second derivatives of the basis functions can be derived as follows.

Using the change of variables, we rewrite the basis functions as

$$\phi_{i,1}(t) = t^{2} (3\Delta_{i-1}-2t)/\Delta_{i-1}^{3}$$

$$\psi_{i,1}(t) = t^{2} (t-\Delta_{i-1})/\Delta_{i-1}^{2}$$

$$\phi_{i,0}(t) = (\Delta_{i-1}-t)^{2} (\Delta_{i-1}+2t)/\Delta_{i-1}^{3}$$

$$\psi_{i,0}(t) = t(\Delta_{i-1}-t)^{2} \Delta_{i-1}^{2}$$
(A5)

Then, taking the second derivative with respect to t yields

Therefore, the integrand of the smoothing integral is expressed as

$$[p_{i-1,i}(t)]^2 = \begin{bmatrix} x_i \\ x_{i-1} \end{bmatrix}^T \begin{bmatrix} K_{i-1,i}(t) \end{bmatrix} \begin{bmatrix} x_i \\ x_{i-1} \end{bmatrix}$$
(A7)

where $K_{i-1,i}$ is defined as

$$K_{i-1,i}(\mu) =$$

$$\begin{bmatrix} \psi_{i,1}^{"}(\mu)\phi_{i,1}^{"}(\mu) & , & \phi_{i,1}^{"}(\mu)\psi_{i,1}^{"}(\mu) & , & \phi_{i,1}^{"}(\mu)\phi_{i,0}^{"}(\mu) & , & \phi_{i,1}^{"}(\mu)\psi_{i,0}^{"}(\mu) \\ \psi_{i,1}^{"}(\mu)\phi_{i,1}^{"}(\mu) & , & \psi_{i,1}^{"}(\mu)\psi_{i,1}^{"}(\mu) & , & \psi_{i,1}^{"}(\mu)\phi_{i,0}^{"}(\mu) & , & \psi_{i,1}^{"}(\mu)\psi_{i,0}^{"}(\mu) \\ \phi_{i,0}^{"}(\mu)\phi_{i,1}^{"}(\mu) & , & \psi_{1,0}^{"}(\mu)\psi_{i,1}^{"}(\mu) & , & \psi_{i,0}^{"}(\mu)\phi_{i,0}^{"}(\mu) & , & \psi_{i,0}^{"}(\mu)\psi_{i,0}^{"}(\mu) \\ \psi_{i,0}^{"}(\mu)\phi_{i,1}^{"}(\mu) & , & \psi_{1,0}^{"}(\mu)\psi_{i,1}^{"}(\mu) & , & \psi_{i,0}^{"}(\mu)\phi_{i,0}^{"}(\mu) & , & \psi_{i,0}^{"}(\mu)\psi_{i,0}^{"}(\mu) \\ \end{bmatrix}$$

By utilizing the above equation, the smoothing integral becomes

$$I_{i-1,i} = \begin{bmatrix} x_i \\ x_{i-1} \end{bmatrix} \begin{bmatrix} \int_0^{\Delta_{i-1}} K_{i-1,i}(t) dt \end{bmatrix} \begin{bmatrix} x_i \\ x_{i-1} \end{bmatrix}$$
(A9)

(8A)

Evaluating the above integral, we obtain

$$\int_0^{\Delta_{i-1}} K_{i-1,i}(t) dt =$$

$$\begin{bmatrix} 12/\Delta_{i-1}^{3} & -6/\Delta_{i-1}^{2} & -12/\Delta_{i-1}^{3} & -6/\Delta_{i-1}^{2} \\ -6/\Delta_{i-1}^{2} & 4/\Delta_{i-1} & 6/\Delta_{i-1}^{2} & 2/\Delta_{i-1} \\ -12/\Delta_{i-1}^{3} & 6/\Delta_{i-1}^{2} & 12/\Delta_{i-1}^{3} & 6/\Delta_{i-1}^{2} \\ -6/\Delta_{i-1}^{2} & 2/\Delta_{i-1} & 6/\Delta_{i-1}^{2} & 4/\Delta_{i-1} \end{bmatrix}$$
(A10)

Matrices B_{i-1} and A_{i-1} are defined as follows:

$$A_{i-1} = \begin{bmatrix} 1 & \Delta_{i-1} \\ \\ 0 & 1 \end{bmatrix} \tag{A11}$$

$$B_{i-1} = \begin{bmatrix} -3 & -2 \\ 12\Delta_{i-1} & -6\Delta_{i-1} \\ -2 & -1 \\ -6\Delta_{i-1} & 4\Delta_{i-1} \end{bmatrix}$$
(A12)

where B_{i-1} is a symmetric matrix. Equation (A10) can then be expressed as

$$\begin{bmatrix} -1 & -1 \\ B_{i-1} & -B_{i-1}A_{i-1} \\ -1 & T & -1 \\ (-B_{i-1}A_{i-1})^T & A_{i-1}B_{i-1}A_{i-1} \end{bmatrix}$$
(A13)

where B_{i-1} and A_{i-1} are functions of the variable Δ_{i-1} . By using the above notation, Eq. (A9) is rewritten as

$$\begin{bmatrix} x_{i} \\ x_{i-1} \end{bmatrix}^{\mathsf{T}} \begin{bmatrix} -1 & -1 & -1 \\ B_{i-1} & -B_{i-1}A_{i-1} \\ T & T & T & -1 \\ -A_{i-1}B_{i-1} & A_{i-1}B_{i-1}A_{i-1} \end{bmatrix} \begin{bmatrix} x_{i} \\ X_{i-1} \end{bmatrix}$$

$$= \begin{bmatrix} x_{i-1} \\ x_{i} \end{bmatrix} \begin{bmatrix} T_{-1} & T_{-1} \\ A_{i-1}B_{i-1}A_{i-1} & -A_{i-1}B_{i-1} \\ -1 & -1 \\ -B_{i-1}A_{i-1} & B_{i-1} \end{bmatrix} \begin{bmatrix} x_{i-1} \\ x_{i} \end{bmatrix}$$

$$= \begin{bmatrix} x_{i-1} \\ x_i \end{bmatrix}^{\mathsf{T}} \begin{bmatrix} \mathsf{T} \\ -\mathsf{A}_{i-1} \\ \mathsf{I} \end{bmatrix} \mathsf{B}_{i-1} \begin{bmatrix} -\mathsf{A}_{i-1} & \mathsf{I} \\ \mathsf{x}_i \end{bmatrix} \begin{bmatrix} x_{i-1} \\ \mathsf{x}_i \end{bmatrix}$$

$$= (x_{i} - A_{i-1} \times_{i-1})^{\mathsf{T}} B_{i-1} (x_{i} - A_{i-1} \times_{i-1})$$
 (A14)

or

$$I_{i-1,i} = \begin{bmatrix} x_{i-1} \\ x_i \end{bmatrix} \begin{bmatrix} c_{i-1} & c_{i-1} \\ T & c_{i-1} \end{bmatrix} \begin{bmatrix} x_{i-1} \\ x_i \end{bmatrix}$$
(A15)

where

$$T_{i-1} = \rho A_{i-1} B_{i-1} A_{i-1}$$
 (A16)

$$T_{i-1}^{-1} = -\rho A_{i-1} B_{i-1}$$
 (A17)

$$E_{i-1} = \rho B_{i-1} \tag{A18}$$

Thus, the smoothing integral is transformed into the above quadratic form.

TECHNICAL REPORT INTERNAL DISTRIBUTION LIST

	NO. OF COPIES
CHIEF, DEVELOPMENT ENGINEERING BRANCH ATTN: SMCAR-CCB-D	1
ATTN: SMCAR-CCB-D -DA	1
-DC	1
-DM	i
-DP	i
-DR	i
-DS (SYSTEMS)	1
bo (orotello)	•
CHIEF, ENGINEERING SUPPORT BRANCH	
ATTN: SMCAR-CCB-S	1
-SE	1
CHIEF DECEMBANCE	
CHIEF, RESEARCH BRANCH ATTN: SMCAR-CCB-R	2
-R (ELLEN FOGARTY)	1
-R (ELLEN FOGARIT)	1
-RM	1
-RP	1
-RT	1
-N1	•
TECHNICAL LIBRARY	5
ATTN: SMCAR-CCB-TL	
	_
TECHNICAL PUBLICATIONS & EDITING UNIT	2
ATTN: SMCAR-CCB-TL	
DIRECTOR, OPERATIONS DIRECTORATE	1
ATTN: SMCWV-OD	•
DIRECTOR, PROCUREMENT DIRECTORATE	1
ATTN: SMCWV-PP	
DIRECTOR, PRODUCT ASSURANCE DIRECTORATE	1
ATTN: SMCWV-QA	*
The second secon	

NOTE: PLEASE NOTIFY DIRECTOR, BENET WEAPONS LABORATORY, ATTN: SMCAR-CCB-TL, OF ANY ADDRESS CHANGES.

TECHNICAL REPORT EXTERNAL DISTRIBUTION LIST

	NO. OF COPIES		NO. OF COPIES
ASST SEC OF THE ARMY RESEARCH AND DEVELOPMENT ATTN: DEPT FOR SCI AND TECH THE PENTAGON WASHINGTON, D.C. 20310-0103	1	COMMANDER ROCK ISLAND ARSENAL ATTN: SMCRI-ENM ROCK ISLAND, IL 61299-5000	1
ADMINISTRATOR DEFENSE TECHNICAL INFO CENTER ATTN: DTIC-FDAC CAMERON STATION	12	DIRECTOR US ARMY INDUSTRIAL BASE ENGR ACTOR ACT	TV 1
ALEXANDRIA, VA 22304-6145 COMMANDER US ARMY ARDEC ATTN: SMCAR-AEE	. 1	COMMANDER US ARMY TANK-AUTMV R&D COMMAND ATTN: AMSTA-DDL (TECH LIB) WARREN, MI 48397-5000	1
SMCAR-AES, BLDG. 321 SMCAR-AET-O, BLDG. 351N SMCAR-CC SMCAR-CCP-A	1 1 1 1	COMMANDER US MILITARY ACADEMY ATTN: DEPARTMENT OF MECHANICS WEST POINT, NY 10996-1792	1
SMCAR-FSA SMCAR-FSM-E SMCAR-FSS-O, BLDG. 94 SMCAR-MSI (STINFO) PICATINNY ARSENAL, NJ 07806-5000	1 1 1 2	US ARMY MISSILE COMMAND REDSTONE SCIENTIFIC INFO CTR ATTN: DOCUMENTS SECT, BLDG. 4484 REDSTONE ARSENAL, A'_ 35898-5241	2
DIRECTOR US ARMY BALLISTIC RESEARCH LABORA ATTN: SLCBR-DD-T, BLDG. 305 ABERDEEN PROVING GROUND, MD 21005	1	COMMANDER US ARMY FGN SCIENCE AND TECH CTI ATTN: DRXST-SD 220 7TH STREET, N.E. CHARLOTTESVILLE, VA 22901	₹ 1
DIRECTOR US ARMY MATERIEL SYSTEMS ANALYSIS ATTN: AMXSY-MP ABERDEEN PROVING GROUND, MD 21005 COMMANDER HQ, AMCCOM ATTN: AMSMC-IMP-L	1	COMMANDER US ARMY LABCOM MATERIALS TECHNOLOGY LAB ATTN: SLCMT-IML (TECH LIB) WATERTOWN, MA 02172-0001	2
ROCK ISLAND, IL 61299-6000			

NOTE: PLEASE NOTIFY COMMANDER, ARMAMENT RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER, US ARMY AMCCOM, ATTN: BENET WEAPONS LABORATORY, SMCAR-CCB-TL, WATERVLIET, NY 12189-4050, OF ANY ADDRESS CHANGES.

THE PROPERTY OF THE PROPERTY O

TECHNICAL REPORT EXTERNAL DISTRIBUTION LIST (CONT'D)


	NO. OF COPIES		NO. OF COPIES
COMMANDER		COMMANDER	
US ARMY LABCOM, ISA		AIR FORCE ARMAMENT LABORATORY	
ATTN: SLCIS-IM-TL	1	ATTN: AFATL/MN	1
2800 POWDER MILL ROAD		EGLIN AFB, FL 32543-5434	
ADELPHI, MD 20783-1145			
		COMMANDER	
COMMANDER		AIR FORCE ARMAMENT LABORATORY	
US ARMY RESEARCH OFFICE		ATTN: AFATL/MNG	
ATTN: CHIEF, IPO	1	EGLIN AFB, FL 32542-5000	1
P.O. BOX 12211			
RESEARCH TRIANGLE PARK, NC	27709-2211	METALS AND CERAMICS INFO CTR	
		BATTELLE COLUMBUS DIVISION	
DIRECTOR		505 KING AVENUE	
US NAVAL RESEARCH LAB		COLUMBUS, OH 43201-2693	1
ATTN: DIR, MECH DIV	1		
CODE 26-27 (DOC LIB)	1		
WASHINGTON, D.C. 20375			

NOTE: PLEASE NOTIFY COMMANDER, ARMAMENT RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER, US ARMY AMCCOM, ATTN: BENET WEAPONS LABORATORY, SMCAR-CCB-TL, WATERVLIET, NY 12189-4050, OF ANY ADDRESS CHANGES.



THE C2 CONTINUITY OF PIECEHISE CUBIC HERMITE
POLYMOMIALS WITH UNEQUAL INTERVALS(U) ARMY ARMAMENT
RESEARCH DEVELOPMENT AND ENGINEERING CENTER MAT.
C N SHEN JUL 87 ARCCB-TR-87819
F/G 12/1 UNCLASSIFIED

AD-A183 351



ERRATA

11 February 1988

ERRATA SHEET (Change Notice)

C1 TO: TECHNICAL REPORT ARCCB-TR-87019

THE C² CONTINUITY OF PIECEWISE CUBIC HERMITE POLYNOMIALS WITH UNEQUAL INTERVALS

by

C. N. SHEN

Please remove pages 1 through 4 from above publication and insert new pages enclosed. Corrections have been made to Equations 2, 9, 10, and 11 on pages 1 and 3.

US ARMY ARMAMENT RESEARCH, DEVELOPMENT,
AND ENGINEERING CENTER

CLOSE COMBAT ARMAMENTS CENTER

BENET LABORATORIES

WATERVLIET, N.Y. 12189-4050

INTRODUCTION

The smoothing of gradients can be obtained by using an optimization method for approximation involving spline functions. A nonuniform grid may be employed to compute by the spline function method with cubic hermite polynomials. Continuous second derivatives at the grid point from both sides are essential for the purpose of smoothing. This method can be applied to solve the following problems: whether the platform can climb on the estimated in-path slope or whether it will tip over the estimated cross-path slope.

RECURSIVE FILTERING AND SMOOTHING PROCEDURE

A spline function $s(\xi)$ is a solution to the optimization problem

where for clarity and simplicity in discussion, we cally consider the cubic spline case. A higher order polynomial spline can also be treated in a similar manner with more complicated computations.

A cubic spline, s, is a piecewise polynomial of class C^2 which has many good properties, such as the minimum norm property and local base property (refs 1,2). From the approximation theory, we know that for each set $A = \{a_1, \ldots, a_N, a_1', a$

$$S(\beta_i;A) = a_i , i = 1,2,...,N$$
 (2)

$$\dot{s}(\beta_i;A) = a'_i, i = 1,N$$
 (3)

where s is the first derivative of the function s. The above equations can be

Ahlberg, J. H., Nilson, E. N., and Walsh, J. L., <u>The Theory of Splines and Their Applications</u>, Academic Press, Inc., 1967.

²Schumaker, L. L., <u>Spline Functions: Basic Theory</u>, John Wiley & Sons, 1981.

thought of as boundary conditions for the piecewise cubic spline interpolation given a set of data (β_i, a_i) , for i = 1, 2, ..., N. Thus, solving the problem in Eq. (1) is equivalent to determining a set of constraints A for the optimization problem:

$$J^* = Min \left\{ \sum_{i=1}^{N} [s(\xi_i; A) - m_i]^T R_i^{-1} [s(\xi_i; A) - m_i] + \rho \sum_{i=2}^{N} \sum_{\beta_{i-1}}^{\beta_i} [s(\xi; A)]^2 d\xi \right\}$$
(4)

Instead of taking a direct approach to find an optimal set of constraints for the problem above, it is proposed to further transform this problem into a form which is convenient to be solved. From the theory of numerical analysis (ref 3), it is well known that a piecewise cubic Hermite polynomial $p(\xi)$ is in the family of C¹. For each set $B = AuA^C$, where A^C is a complement of A, i.e., $A^C = \{a'_i, i = 2,3,...,N-1\}$, then $B = \{a_i,a'_i, i=1,2,...,N\}$, there exists a unique piecewise cubic Hermite polynomial $p(\xi;A)$ such that

$$p(\beta_i; B) = a_i , i = 1, 2, ..., N$$
 (5)

$$\dot{\rho}(\beta_{\dot{1}};B) = a'_{\dot{1}} , \quad \dot{1} = 2, \dots, N \tag{6}$$

where p is the first derivative of p.

It should also be noted that for each set A, there are an infinite number of piecewise Hermite polynomials $p(\xi;A)$ such that

$$p(\beta_i; A) = a_i$$
 , $i = 1, 2, ..., N$ (7)

$$\dot{p}(\beta_i;A) = a'_i , \quad i = 1,N$$
 (8)

Let a set of $p(\xi;A)$ which satisfies the constraints in the equations above be P, i.e.,

$$P = \{p(\xi;A): (5), (6) \text{ satisfied}\}$$
 (9)

Burden, R. L. et al., Numerical Analysis, Prindle, Weber, & Schmidt, 1978.

Referring to the paper by de Boor (ref 4), it is noted that there exists a unique cubic spline $s(\xi;A)$ in the set P. Also from the minimum norm property of a cubic spline, we have the following relation:

That is

$$\begin{array}{cccc}
N & \beta_{i} & \dots \\
\Sigma & \int & [s(\xi;A)]^{2}d\xi = \inf & J_{p}(p) \\
i=2 & \beta_{i-1} & p \in P
\end{array} \tag{10}$$

where

$$J_{p} = \sum_{i=2}^{N} \int_{\beta_{i-1}}^{\beta_{i}} [p(\xi;A)]^{2}d\xi \qquad (11)$$

Since a cubic spline $s(\xi;A)$ is unique, a piecewise cubic Hermite polynomial $p(\xi;A)$ which minimizes the smoothing integral J_p in the above equation with respect to A^c becomes a cubic spline $s(\xi;A)$. To be more precise, we have the following theorem.

THEOREM: Let P represent a set of piecewise cubic Hermite polynomials p which satisfies the constraints below:

$$p(\beta_i; A^c) = a_i , i = 1, 2, ... N$$
 (12)

$$\dot{p}(\beta_i; A^C) = a^i, \quad i = 1, N \tag{13}$$

where p ϵ C1, A, and AC are the same as mentioned before. Then there exists a unique cubic spline s(ξ) such that

where s and p are the second derivatives of functions s and p and s ϵ C2. A simple example with N = 3 is given next.

de Boor, C., "Bicubid Spline Interpolation," J. Math Phys., Vol. 41, 1962, pp. 212-218.

EXAMPLE FOR C* CONTINUITY

For convenience and simplicity, we only consider a special case with N = 3. The node points are given as β_1 , β_2 , and β_3 . The intervals are not equal, i.e.,

$$(\beta_2 - \beta_1) \neq (\beta_3 - \beta_2) \tag{15}$$

Let a set of piecewise cubic Hermite polynomials p be

$$P = [p(t;A^{C}), p \in C^{1}[t_{1},t_{3}], \dot{p}(t_{2}) = a, a \in A^{C}]$$
 (16)

which satisfies the constraints in the equations below:

$$p(t_i;A^C) = a_i$$
 , for $i = 1,2,3$
 $\dot{p}(t_i;A^C) = a'_i$, for $i = 1,3$ (17)

In this special case, a set $A^{C} = a_{2}^{C} = a_{2}^{C}$

We want to show here that the cubic Hermite polynomial $p(t;A^C)$, which is obtained by minimizing the smoothing integral, will become a cubic spline function $s(t) \in C^2[t_1,t_3]$

$$J^* = \min_{A^C} \left\{ \int_{t_1}^{t_2^-} [p(t;A^2)]^2 dt + \int_{t_2^+}^{t_3} [p(t;A^C)]^2 dt \right\}$$

$$= \min_{a} \left\{ \int_{t_1}^{t_2^-} [p(t;a)]^2 dt + \int_{t_2^+}^{t_3} [p(t;a)]^2 dt \right\}$$
(18)

From Eq. (A14) of the Appendix, the smoothing integral above can be written as

$$J(a) = (x_2 - A_1 x_1)^{\mathsf{T}} B_1^{-1} (x_2 - A_1 x_1) + (x_3 - A_2 x_2)^{\mathsf{T}} B_2^{-1} (x_3 - A_2 x_2)$$
(19)

where A_i , B_i , and x_i are defined in the Appendix, and

$$x_i = (a_i, a_i)^T$$
, with $a_2 = a$, $i = 1, 2, 3$ (20)

$$\Delta_{i-1} = d_{i-1} = t_i - t_{i-1}$$
 (21)

Using Eqs. (A11) and (A12), the functional J(a) is written as

H ND DATE FILMED MARCH 1988 DTIC